



# P-201R



## Product Description

Single gang electrical box for use with nonmetallic sheathed cable

**Brand:** flexBOX®  
**Catalog #:** P-201R

**Carton Quantity:** 100  
**Carton Weight:** 24 lb.

**Height:** 3-3/4 in.  
**Width:** 2-5/16 in.  
**Depth:** 3-1/16 in.  
**Volume:** 20.5 cu. in.  
**Wall Box**  
**Number of Gangs:** 1

**UPC:** 085339249016  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

### FEATURES

Molded-in splined device holes, offset gauge marks, leveling ribs

### APPLICATION

Manufactured housing construction 2 HR fire resistive walls & ceilings

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Black

### ADDITIONAL MATERIALS

Carbon steel fasteners

### MATERIAL

Polyvinyl Chloride

### MOUNTING

Angled mid nails