



# PC244OWG



## Product Description

4" dia. round fixture support box for use with nonmetallic sheathed cable

**Brand:** flexBOX®  
**Catalog #:** PC244OWG

**Carton Quantity:** 24  
**Carton Weight:** 8 lb.

**Width:** 4 in.  
**Depth:** 3 in.  
**Volume:** 24.5 cu. in.  
**Type of Installation:** Old Work  
**Round Ceiling Box**

**UPC:** 085339974185  
**UNSPSC:** 39121316  
**Patents:**  
U.S. Patent No. 6,365,831 B1  
**Country of Origin:** United States of America

## FEATURES

Machine tapped fixture holes, round exterior for easy cut-in, ground strap

## APPLICATION

Old work residential construction 2 HR fire resistive walls

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Black

## ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

## MATERIAL

Polycarbonate

Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

## MOUNTING

Metal wing brackets/nonmetal ears wall compression

## SUPPORT RATING

Meets NEC for wall applications