









# A-51® Incandescent Factory Sealed Luminaire Accessories

## For Group C and D Locations. Explosionproof

Suitable for use in Wet Locations. UNILETS for use with Threaded Metal Conduit.

Class I, Division 1 and 2, Groups C, D  
Class II, Division 1 and 2, Groups E, F, G  
Class III

Mounting Hoods		
Type	Hub Size (Inches)	Catalog Number
<b>Pendant — One Hub, Rigid or Flexible Mounting</b>		
	1/2	AAP-50
	3/4	AAP-75
	1	AAP-100
<b>Ceiling — Four Hubs, Three Close-up Plugs</b>		
	1/2	AAC-50
	3/4	AAC-75
	1	AAC-100
<b>25° Stanchion — Not UL Listed — One Hub</b>		
	1-1/2	AAN-150 ①
<b>Long Bracket — Four Hubs, Three Close-up Plugs</b>		
	1/2	AALB-50
	3/4	AALB-75
	1	AALB-100
<b>15° Short Bracket — Two Hubs, One Close-up Plug</b>		
	1/2	AASB-50
	3/4	AASB-75
Type	Catalog Number	
<b>Fixture Units</b>		
	60-100 W A-21	AAU-1N
	150-300 W A-23 & PS-25	AAU-15N
	200-300 W PS-30	AAU-2NS
<b>Prismatic Glass Globes</b>		
	60-100 W (AAU-1N)	AAGL-1PR
	150-300 W (AAU-15N)	AAGL-1PR
	200-300 W (AAU-2NS)	AAGL-2PR
<b>Aluminum Guards</b>		
	60-100 W (AAU-1N)	AAGU-1
	150-300 W (AAU-15N)	AAGU-1
	200-300 W (AAU-2NS)	AAGU-2

① 1-1/2" tapped hub furnished with a 1-1/2" to 1-1/4" reducer.