


Straight

Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 1.56
Dimension B in Inches: 1.71
Dimension C in Inches: 1.90

Application

The CSS-050 is specially constructed for pour in place applications. The fitting flange end is designed to be mounted to a concrete form. The open end is then connected to the raceway. After the concrete has cured and the form is removed, the flange covering can then be punctured providing access to a threaded raceway entry point.

Product Information

Material: High Strength Zinc Alloy
Finish: Ball Burnish

Certifications & Codes:

Federal
Specification A-A-50553A
Number:
NEMA
Standard: FB-1
UL File
Number: CSS-050 Listed ETL: Bridgeport
Fittings/CSS-050 Conforms to UL514B
and CSA C22.2 No. 18.3
UL
Standard: UL514B
UNSPSC: 39121311

Catalog ID: CSS-050

UPC Number: 78174792220

Description: 1/2" Rigid threaded concrete encasable flanged fitting

Application: The CSS-050 is specially constructed for pour in place applications. The fitting flange end is designed to be mounted to a concrete form. The open end is then connected to the raceway. After the concrete has cured and the form is removed, the flange covering can then be punctured providing access to a threaded raceway entry point.

Trade Size: 1/2"

Std Pkg Qty: 40

Unit Qty: 10