


| CATALOG NUMBER 2 | AMPS | SCCR | WIRE RANGE | | MAX REQUIRED OVERCURRENT PROTECTION | | | | | |
|--|------|-------|-------------|-------------|-------------------------------------|----------------------|---------------------------------------|-----------------|-----------------|-----------------------------------|
| | | | LINE | LOAD | CLASS J (AJT, A4J, HSJ) | CLASS T (A3T/A6T) | RK1 (A2D/A6D) (A2K/A6K) HSRK | RK5 (TR/TRS) | CLASS G (AG) | CLASS CC (ATDR, ATQR, ATMR) |
| BDB162/0X | 175 | 100kA | (1) 2/0-#14 | (6) #2-#14 | 200A | 200A | 200A | 100A | 60A | 30A |
| BDB11500X | 380 | 100kA | (1) 500-#4 | (1) 500-#4 | 400A | 400A | 400A | 200A | 60A | 30A |
| BDB16500X | 380 | 100kA | (1) 500-#4 | (6) 2/0-#14 | 400A | 400A | 400A | 200A | 60A | 30A |
| BDB22500X | 760 | 100kA | (2) 500-#4 | (2) 500-#4 | 600A | 600A | 600A | 200A | 60A | 30A |
| BDB26500X | 760 | 100kA | (2) 500-#4 | (6) 2/0-#14 | 600A | 600A | 600A | 400A | 60A | 30A |
| BDB212500X | 760 | 100kA | (2) 500-#4 | (12) #4-#14 | 600A | 600A | 600A | 400A | 60A | 30A |
| BDB22350X | 620 | 100kA | (2) 350-#6 | (2) 350-#6 | 600A | 600A | 600A | 200A | 60A | 30A |
| BDB26350X | 620 | 100kA | (2) 350-#6 | (6) 2/0-#14 | 600A | 600A | 400A | 200A | 60A | 30A |
| BDB112350X | 310 | 100kA | (1) 350-#6 | (12) #4-#14 | 400A | 400A | 400A | 200A | 60A | 30A |
| BDB16350X | 310 | 100kA | (1) 350-#6 | (6) 2/0-#14 | 400A | 400A | 400A | 200A | 60A | 30A |
| BDB24500X | 760 | 100kA | (2) 500-#4 | (4) 4/0-#6 | 600A | 600A | 600A | 400A | 60A | 30A |
| BDB22600X | 840 | 100kA | (2) 600-#2 | (2) 600-#2 | 600A | 600A | 600A | 400A | 60A | 30A |

| REV | DATE | DESCRIPTION | ECO | BY | CHK. |
|-----|------------|-------------------------------------|-------|----|------|
| A | 08/28/2013 | CREATE SALES DRAWING AS PER MARK-UP | 33059 | VK | PB |

NOTES:

- UL RECOGNIZED FOR 100kA SCCR WHEN PROTECTED BY FUSES AS SHOWN.
- 2 REPLACE X WITH 1, 2 OR 3 TO DENOTE THE NUMBER OF POLES.
- RATINGS ARE FOR COPPER CONDUCTOR ONLY.

| | | | |
|--|---------------------|---|----------------------|
| TO ORDER BURNDY® PRODUCTS CALL UNITED STATES 1-800-346-4175 (LONDONDERRY, NH) CANADA: 1-800-361-6975 (QUEBEC) 1-800-387-6487 (ALL OTHER PROVINCES) FOR PRODUCT INFO: http://www.burndy.com | | VERSIPOLE FUSE RATINGS | |
| | | ITEM NO: -- | CAT. NO: (SEE TABLE) |
| DRAWN BY: V KAMAL 08/28/13 CHECKER: T REYNOLDS 08/29/13 DSN APRVL: T REYNOLDS 08/29/13 MFG APRVL: -- QA APRVL: C KOWALCZYK 09/04/13 MKT APRVL: M BAILLY 08/29/13 | |  | |
| PROJ #: -- | SIZE: B | DRAWING NO: 50031053 | REV: A |
| DOCUMENT TYPE: SALES | REL LEVEL: Released | SHEET 1 OF 1 | |