


## BURNDY

### POLYMER CABLE TIES

#### STANDARD CABLE TIES




Catalog Number	Maximum Bundle Diameter Inches [mm]	Minimum Tensile Strength Lbs (N)	Width Inches [mm]	Length Inches [mm]
CT18075C	.75 [19]	18 (80)	.10 [2.5]	4.00 [102]
CT18125C	1.25 [32]	18 (80)	.10 [2.5]	5.67 [144]
CT18200C	2.00 [51]	18 (80)	.10 [2.5]	8.00 [203]
CT30125C	1.25 [32]	30 (133)	.14 [3.6]	6.00 [152]
CT40200C	2.00 [51]	40 (178)	.15 [3.8]	8.50 [216]
CT40300C	3.00 [76]	40 (178)	.15 [3.8]	11.50 [292]
CT40400C	4.00 [102]	40 (178)	.15 [3.8]	14.50 [368]
CT50175C	1.75 [44]	50 (222)	.18 [4.6]	8.00 [203]
CT50300C	3.00 [76]	50 (222)	.18 [4.6]	11.75 [298]
CT50400C	4.00 [102]	50 (222)	.18 [4.6]	15.50 [394]
CT120200L	2.00 [51]	120 (534)	.30 [7.6]	8.87 [226]
CT120300L	3.00 [76]	120 (534)	.30 [7.6]	11.87 [302]
CT120400L	4.00 [102]	120 (534)	.30 [7.6]	15.25 [387]
CT120900L	9.00 [229]	120 (534)	.30 [7.6]	29.75 [776]
CT175400Q	4.00 [102]	175 (778)	.35 [8.9]	15.00 [381]
CT175600Q	6.00 [152]	175 (778)	.35 [8.9]	21.00 [533]
CT175900Q	9.00 [229]	175 (778)	.35 [8.9]	32.00 [813]
CT1751100Q	11.00 [279]	175 (778)	.35 [8.9]	6.00 [914]
CT1751400Q	14.00 [356]	175 (778)	.35 [8.9]	52.00 [1321]
CT250600Q	6.00 [152]	250 (1112)	.50 [12.7]	23.00 [584]
CT250800Q	8.00 [203]	250 (1112)	.50 [12.7]	29.00 [737]
CT2501000Q	10.00 [254]	250 (1112)	.50 [12.7]	35.00 [889]
CT2501200Q	12.00 [305]	250 (1112)	.50 [12.7]	40.00 [1016]

#### HEAVY DUTY RELEASABLE CABLE TIES

CT250200RQ	2.00 [51]	250 (1112)	.50 [12.7]	9.00 [229]
CT250500RQ	5.00 [127]	250 (1112)	.50 [12.7]	20.00 [508]
CT250600RQ	6.00 [152]	250 (1112)	.50 [12.7]	23.00 [584]
CT250800RQ	8.00 [203]	250 (1112)	.50 [12.7]	29.00 [737]
CT2501000RQ	10.00 [254]	250 (1112)	.50 [12.7]	35.00 [889]

#### IDENTIFICATION CABLE TIES



Catalog Number	Marking Pad Size Inches	Maximum Bundle Diameter Inches [mm]	Minimum Tensile Strength Lbs (N)	Length Inches [mm]
CT18075IDC	1x9/64	.75 [19]	18 (80)	4.00 [102]
CT18075FLC	13/16x5/16	.75 [19]	18 (80)	4.25 [108]
CT50175IDC	1x7/16	1.75 [44]	50 (222)	8.00 [203]
CT50175ID2L	1-11/16x5/16	1.75 [44]	50 (222)	8.00 [203]
CT50175ID3L	1-13/16x5/16	1.75 [44]	50 (222)	8.00 [203]
CT50400IDC	1/2x2-1/8	4.00 [102]	50 (222)	15.00 [381]

#### MOUNTING HOLE CABLE TIES



Catalog Number	Screw Size	Maximum Bundle Diameter Inches [mm]	Minimum Tensile Strength Lbs (N)
CT18075MH4C	#4 (M2.5)	.75 [19]	18 (80)
CT30125MH8C	#8 (M4)	1.25 [32]	30 (133)
CT50175MH10C	#10 (M5)	1.75 [44]	50 (222)
CT50400MH10C	#10 (M5)	4.00 [102]	50 (222)
CT120400MH14L	1/4 (M6)	4.00 [102]	120 (534)

#### HALOGEN FREE CABLE TIES



Catalog Number	Maximum Bundle Diameter Inches [mm]	Minimum Tensile Strength Lbs (N)	Width Inches [mm]	Length Inches [mm]
CTH18075C	.75 [19]	18 (80)	4.00 [102]	.10 [2.5]
CTH30200C	2.00 [51]	30 (133)	8.00 [203]	.14 [3.6]
CTH50175C	1.75 [44]	50 (222)	8.00 [203]	.18 [4.6]
CTH120400L	4.00 [102]	120 (534)	15.25 [387]	.18 [4.6]

#### HOOK AND LOOP STRAPS

Reusable and flexible, hook and loop straps are a self-gripping fastening system.

These ties are specifically used on fiberoptic applications.

The TFV-V2 flame retardant straps are UL Listed Wire Positioning Devices (ZODZ), UL94-V2 rated for use in air handling spaces in accordance with the NEC section 300-22 (c) and (d). Perfect for plenum areas.

25 straps are packaged in each polybag.



Catalog Number	Product Description	Maximum Bundle Dia.	Avg. Sheer (PSI)
TFV3B12V2**	3/4x12, Black, 25pk	3.0	29
TFV3B18V2**	3/4x18, Black, 25pk	5.0	29
TFV3B6V2**	3/4x6, Black, 25pk	1.0	23
TFV3BLU12	3/4x12, Royal Blue, 25pk	3.0	23
TFV3BLU18	3/4x18, Royal Blue, 25pk	5.0	23

\*\* UL94-V2 listed



#### BURNDY® UNIRAP™ Cable Ties:

- One piece Nylon with no metal parts
- Straps are tough, lightweight and abrasion resistant
- High tensile strength
- Self locking
- Compact heads with pre-bent tips



Experience. Technology. Answers.™

1-800-346-4175 • International : +1 (603) 222-5330  
www.burndy.com