



BURNDY Catalog Number
UPC Number
Description
Status

ES25R25R
7818101493000
1/0-1/0 ACSR INS SE CONN
Active

Web Use
BURNDY Product Line

Product Description

General

Insulated AL service entrance compression sleeve for combinations of insulated CU, AL and ACSR conductors, Color Code: Yellow (Side A), Yellow (Side B)

Conductor(s)

ACSR Size (Side A) - Range	1 (6/1) Robin AWG-1/0 (6/1) Raven AWG
Copper Solid Size (Side A) - Range	N/A
ACSR Size (Side B) - Range	1 (6/1) Robin AWG-1/0 (6/1) Raven AWG
Copper Str Size(Side B) - Range	1/0 AWG
Aluminum Size (Side A) - Range	1/0 AWG-1 AWG (19 Str.)
Copper Str Size (Side A) - Range	1/0 AWG-1 AWG (19 Str.)
Aluminum Size (Side B) - Range	1/0 AWG-1 AWG (19 Str.)
CopperSolid Size (Side B) - Range	N/A

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Physical

Color Code (Side A)	Yellow
Color Code (Side B)	Yellow
Insulation Type	Nylon
Insulated (Yes or No)	Y

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175

