



GA25H26

by Burndy
Catalog ID: GA25H26

Prop 65 Notice

Cast Copper Alloy Ground Clamp for 'H' Beam, 4 Sol. - 2/0 Str, 4 in W.

Features: High Copper Alloy Ground Connector For Joining A Wide Range Of Cable Parallel To H Beams Or Square Tube, Hardware Is Made From DURUM For Superior Corrosion Protection, Width: 4 IN, Installation Torque: 240 IN-LB, Outer Dimension Of H Beam Or Tube: 1-7/8 X 1-7/8 IN Minimum, 2-1/2 X 2-1/2 IN Maximum, Height: 4-3/4 IN

Product Details

General

Application	For Joining A Wide Range Of Copper Cable Parallel To H Beams Or Square Tube
Installation Torque Recommended Run in-lb	240 Lb in
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Type	GA-H
UPC	781810001677
UPC 12 Digit	7818100016777

Dimensions

Dimension - Height fraction	4-3/4 in
Dimension - Height inch	4.75 in
Dimension - Width inch	4.00 in
Dimension - Width mm	102 mm

Conductor Related

Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Size	2/0 AWG
Conductor - Copper Str Size Range	2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • CU C Solid-Size • CU C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	6
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)