



GZ2658

by Burndy Catalog ID: GZ2658

Prop 65 Notice

Cast Cu Alloy Ground Clamp, Cable to Bar, #3 - 2/0 AWG Str, 5/8" Bolt

High Copper Alloy Ground Connector For Joining A Wide Range Of Cable To 1/4 IN Thick Bar, Cable Is Gripped By Curving It Around The Clamping Bolt In Connector Groove, UL467 Listed, The High Copper Alloy Cast Body And DURIUM Bolts, Nuts, And Lockwashers Make Them Suitable For Direct Burial In Concrete Or Ground, Width: 1-3/4 IN, Installation Torque: 660 IN-LB, Bar Thickness: 1/4 IN, Height: 2-1/4 IN

Product Details

General

Application	For Joining A Wide Range Of Copper Cable To Bar, Direct Burial In Concrete Or Ground
Construction Material - Main	Copper
Installation Torque Recommended in-Ib	660 LBS/in
Material	Copper
Material Type - Screw	DURIUM™ Silicon Bronze
Plated	Ν
Plating Type	Unplated
Sub Brand	MECHANICAL CONNECTOR
Туре	GZ
UPC	781810990148
UPC 12 Digit	7818109901488

Dimensions

Dimension - Height fraction	2-1/4
Dimension - Height inch	2.25 in
Dimension - L Length Overall mm	48 mm
Dimension - Length Overall inch	1.88 in
Dimension - Width fraction	1-3/4 in
Dimension - Width inch	1.75 in
Dimension - Width mm	44 mm

Conductor Related

Conductor - Copper Str Size	3;2;1;1/0;2/0
Conductor - Copper Str Size Range	3-2/0

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No

Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)