



BURNDY Catalog Number
UPC Number
Description
Status

KK3A36U4N
 7818103704699
 THREE:2STR-600 NEMA
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in)	4.22
Length (in)	5.50
Bolt Hole Size (in)	0.56
Thickness	0.38
D - in	3.00
Pad Width (in)	4.22
E - in	1.75
N (in)	0.63

General

Number of Conductors	3
Number of Holes	4
Product Description	Aluminum Universal Terminal, 3 Conductor, 4 Hole, 2 AWG (Str)-600 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 6 Screws, Al/Cu Rated, Tin Plated

Conductor(s)

Aluminum Size (Range)	2 STR - 600 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	2 AWG-600 kcmil

Physical

Installation Torque	375
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	9/16
Plated (Yes or No)	Y
Product Material	Aluminum

Approvals / Certifications

Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175