



BURNDY Catalog Number	KVSU31
UPC Number	781810082553
Description	UNIV OKLIP 250-300/6-350
Status	Active

Web Use
BURNDY Product Line

General	
Product Description	Mechanical Connector, Cable to Cable, Cu/Al: 250-350 kcmil (Run), 6 AWG-350 kcmil (Tap), ASCR: 4/0 AWG-300 kcmil (Run), 6 AWG-300 kcmil (Tap)
Conductor(s)	
ACSR Compact Tap (Range)	N/A
Aluminum Run Size (Range)	250 kcmil-350 kcmil
AAAC 5005 Tap (Range)	30.58 (7) kcmil-394.5 (19) kcmil
Copper Tap Range	6 AWG-350 kcmil
CopperWeld Solid Run Size (Range)	N/A
Copper Stranded Run (Range)	250 kcmil-350 kcmil
CopperWeld Stranded Tap Size (Range)	N/A
AAAC 6201 Run (Range)	246.9 (7) kcmil-394.5 (19) kcmil
CopperWeld Solid Tap Size (Range)	N/A
ACSR Compact Run (Range)	N/A
Aluminum Tap Size (Range)	6 AWG-350 kcmil
AAAC 5005 Run (Range)	246.9 (7) kcmil-394.5 (19) kcmil
Galvanized Steel Size (Range)	9/16 (19) in-5/8 (19) in
CopperWeld Stranded Run Size (Range)	N/A
AAAC 6201 Tap (Range)	30.58 (7) kcmil-394.5 (19) kcmil
Approvals / Certifications	
UL Listed	N
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Physical	
Installation Torque	325
Type of Plating	Tin - Electro Plated
Plated (Yes or No)	Y
Product Material	Copper Alloy
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Services
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175

