




BURNDY Catalog Number
UPC Number
Description
Status

KVSU31
 7818100825533
 UNIV OKLIP 250-300/6-350
 Active

Web Use
 BURNDY Product Line



General

Product Description

Tin-plated copper alloy connector with tin plated silicon bronze hardware. Spacer bar separates dissimilar conductors and provides long contact length, Tightening torque: 325 in -lb, wrench size: 3/4 cross flats

Conductor(s)

Aluminum Run Size (Range) 250 kcmil-350 kcmil
 Copper Tap Range 6 AWG-350 kcmil
 CopperWeld Solid Run Size (Range) -
 Copper Stranded Run (Range) 250 kcmil-350 kcmil
 CopperWeld Stranded Tap Size (Range) #6 - 4/0
 CopperWeld Solid Tap Size (Range) #6 - 4/0
 Aluminum Tap Size (Range) 6 AWG-350 kcmil
 Galvanized Steel Size (Range) 9/16 (19) in-5/8 (19) in
 CopperWeld Stranded Run Size (Range) -

Approvals / Certifications

UL Listed N
 CSA Certified Y
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N

Physical

Installation Torque 325
 Type of Plating Tin
 Plated (Yes or No) Y
 Product Material Copper Alloy

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175