



KVS34

by Burndy
Catalog ID: KVS34

Prop 65 Notice

Mechanical Connector For CUWeld and Copper Supplied with a CU alloy Spacer that separates run and tap conductors, Recommended Torque: 375 LBS.

Features: Type KVS Except For A High Copper Alloy Spacer That Separates Run And Tap Conductors, Provides High Contact Pressure, Confines Conductor Strands, And Assures Vibration-Proof Connection, Longer Peened Bolt, Permits Swivel Action For Easier Installation, Silicon Bronze DURUM Hardware, Conductor Type: Run: Copperweld, Commercial Stranded Copper, Installation Torque: 375 IN-LB, Conductor Spacer: Yes

Product Details

General

Application	For Copper And Copperweld Conductors
Installation Torque Recommended in-lb	480 LBS/in
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	OKLIP
Trade Name	OKLIP™
Type	KVSW
UPC	781810067307
UPC 12 Digit	7818100673077

Dimensions

Dimension - Height inch	3.06 in
Dimension - Length Overall inch	1.34 in
Dimension - Stud Size inch	1/2 in
Dimension - Width inch	2.20 in

Conductor Related

Conductor - Copper Str Run	400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Run Range	400 kcmil - 500 kcmil
Conductor - Copper Str Tap	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Tap Range	4 str. - 500 kcmil
Conductor Type	CU C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)