



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YAG34L2NTCLD  
 7818100182000  
 CULUG-350FLEX-NEMA-LDPLT  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	5.11
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.23
B Length (in)	1.27
Pad Width (in)	1.55
E - in	1.75
Strip Length	1-5/16

**General**

Number of Holes	2
Product Description	Cu Comp Terminal Flex Cond, Bvl Entry, 2 Hole/W/O/InspWindow, 373.7(925/#24)DLO, 350 kcmil Flex, 600 V-35 kV, 1/2" Stud, 1.75" Spacing, Std bbl, Lead Plated

**Conductor(s)**

Flex (Class H) Size - Range	350 kcmil
Flex (Class I) Size - Range	350 kcmil
DLO Size (Range)	373.7 (925/#24) DLO
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	N/A
Flex (Class G) Size - Range	350 kcmil
Flex (Class M) Size - Range	350 kcmil
CopperWeld Stranded Size (Range)	N/A

**Physical**

Type of Plating	Lead
Bolt Hole Size	1/2
Color Code	Blue
Plated (Yes or No)	Y
Index Number	19
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175

