



BURNDY Catalog Number	YGHP34C34
UPC Number	781810220986
Description	250-500 TO 350-500 GRN C
Status	Active

Web Use
BURNDY Product Line

Dimensional	
B Length (in)	2.75
B Length (Fraction)	2-3/4
General	
Product Description	Copper Compression Fig. 6 Connector, 250-500 kcmil or 5/8" - 3/4" Rod (Run) / 350 -500 kcmil (Tap)
Prefilled (Oxide Inhibitor)	Y
Other	
Type of Oxide Inhibitor	Penetrox E
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467,IEEE 837
Conductor(s)	
Copper Tap Range	350 kcmil-500 kcmil
Copper Stranded Run (Range)	250 kcmil-500 kcmil
Copper Solid Tap (Range)	N/A
Copper Solid Run Size (Range)	N/A
Physical	
Type of Plating	Unplated
Connector Type	Tap
Plated (Yes or No)	N
Index Number	1011
Product Material	Copper
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175