



BURNDY Catalog Number
UPC Number
Description
Status

YGHP34C34
 7818102209866
 250-500 TO 350-500 GRN C
 Active

Web Use
 BURNDY Product Line

B Length (in)
 B Length (Fraction)

Dimensional
 1.10
 1-1/10

Product Description
 Prefilled (Oxide Inhibitor)

General
 Cu Compression Ground Rod
 Connector, 350 Kcmil - 500 Kcmil,
 5/8" - 3/4" Rod Dia
 Y

Type of Oxide Inhibitor

Other
 Penetrox E

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications

Y
 Y
 Y
 Compliant
 N
 N
 UL467,IEEE 837

Copper Tap Range
 Copper Stranded Run (Range)
 Copper Solid Tap (Range)
 Copper Solid Run Size (Range)

Conductor(s)
 350 kcmil-500 kcmil
 250 kcmil-500 kcmil
 N/A
 N/A

Type of Plating
 Connector Type
 Plated (Yes or No)
 Index Number
 Product Material

Physical
 Unplated
 Tap
 N
 1011
 Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175