

Flexible Metallic Conduit Fittings

Clamp Type – Malleable Iron

CLAMP TYPE 45° ANGLE – MALLEABLE IRON

Applications:

- Used to clamp and secure AC/MC cable to a box or enclosure

Features:

- High strength malleable iron
- 105°C temperature rating
- Used with armoured cable and flexible metal conduit
- Male hub threads – NPSM

Standard Materials:

- Malleable iron
- Steel locknut
- Stamped steel covers

Standard Finish:

- Zinc plated

Clamp Type 45° Angle – Non-insulated

UL File No. E-19188 or E-19189



Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100	
723*	$\frac{3}{8}$ "	$\frac{21}{32}$ "	$\frac{17}{32}$ "	50	14	
		For 2 conductor Nos. 14, 12, 10 3 conductor Nos. 14, 12, 10 4 conductor Nos. 14, 12 Flexible metallic conduit $\frac{5}{16}$ " and $\frac{3}{8}$ "				
735	$\frac{1}{2}$ "	$\frac{15}{16}$ "	$\frac{9}{16}$ "	25	18	
		For 2 conductor No. 8 Flexible metallic conduit $\frac{1}{2}$ "				
737*	$\frac{3}{4}$ "	$1\frac{1}{8}$ "	$\frac{25}{32}$ "	25	24	
		For 2 conductor Nos. 6, 4 3 conductor Nos. 6, 4 Flexible metallic conduit $\frac{3}{4}$ "				

*UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™)
MCAP™ is a registered trademark of Southwire Company.

Clamp Type 45° Angle – Insulated

UL File No. E-19188 or E-19189



Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
1723*	$\frac{3}{8}$ "	$\frac{21}{32}$ "	$\frac{17}{32}$ "	50	14
1735	$\frac{1}{2}$ "	$\frac{15}{16}$ "	$\frac{9}{16}$ "	25	17
1737*	$\frac{3}{4}$ "	$1\frac{1}{8}$ "	$\frac{25}{32}$ "	25	24

*UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).
MCAP™ is a registered trademark of Southwire Company.

Flexible Metallic Conduit Fittings

Clamp Type – Malleable Iron

CLAMP TYPE 90° ANGLE – MALLEABLE IRON

Applications:

- Used to clamp and secure AC/MC cable to a box or enclosure

Features:

- High strength malleable iron
- 105°C temperature rating
- Used with armoured cable and flexible metal conduit
- Male hub threads – NPSM

Standard Materials:

- Malleable iron
- Steel locknut
- Stamped steel covers

Standard Finish:

- Zinc plated

Clamp Type 90° Angle – Insulated

UL File No. E-19188 or E-19189



Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
1736†	1/2"	15/16"	9/16"	25	19
1738†*	3/4"	1 1/8"	13/16"	20	31
1739	1"	1 13/32"	1"	5	50
1740	1 1/4"	1 21/32"	1 1/4"	2	113
1741	1 1/2"	1 7/8"	1 1/2"	1	188
1742	2"	2 1/2"	1 15/16"	1	236
1744	2 1/2"	3"	2 1/2"	1	400
1745	3"	3 1/2"	3"	1	600
1746	3 1/2"	4"	3 13/32"	1	1150
1747	4"	4 19/32"	3 31/32"	1	1460

†Suitable for use with armoured cable.

*UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).

MCAP™ is a registered trademark of Southwire Company.

Clamp Type* 90° Angle – Non-insulated

UL File No. E-19188 or E-19189



Cat. #	Trade Size	Dia. of Opening for Cable	Dia. of Bushed Hole	Unit Qty.	Wt. Lbs. Per 100
724†§	3/8"	2 1/32"	1 7/32"	50	15
For 2 conductor Nos. 14, 12, 10 3 conductor Nos. 14, 12, 10 4 conductor Nos. 14, 12 Flexible metallic conduit 5/16" and 3/8"					
736†	1/2"	15/16"	9/16"	25	19
738†§	3/4"	1 1/8"	13/16"	20	31
739	1"	1 13/32"	1"	5	50
740	1 1/4"	1 21/32"	1 1/4"	2	113
741	1 1/2"	1 7/8"	1 1/2"	1	188
742	2"	2 1/2"	1 15/16"	1	236
744	2 1/2"	3"	2 1/2"	1	400
745	3"	3 1/2"	3"	1	600
746	3 1/2"	4"	3 13/32"	1	1150
747	4"	4 19/32"	3 31/32"	1	1460

*UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b).

†Suitable for use with armoured cable.

§UL approved for use with aluminum interlocking grounding metal-clad cable, Type MCIA (Southwire MCAP™).

MCAP™ is a registered trademark of Southwire Company.