



AHB

WATER PIPE HEATING CABLE, FIXED RESISTANCE, PRE-TERMINATED



Each AHB cable consists of a tough XLPE inner insulation, a continuous ground braid and weather resistant PVC outer jacket. AHB units are activated and de-activated by an integral energy-saving thermostat. Each cable is UL Listed to Canadian Safety Standards and CSA Certified when used in accordance with instructions on water-filled metal or plastic pipes.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
AHB013A ①	0.91m (3ft), 21 Watts	5	2.7kg (6lb)	0-13627-18874-7	 
AHB016A ①	1.83m (6ft), 42 Watts	5	3.2kg (7lb)	0-13627-18875-4	
AHB019A ①	2.74m (9ft), 63 Watts	5	4.1kg (9lb)	0-13627-18876-1	
AHB112A ①	3.66m (12ft), 84 Watts	5	4.5kg (10lb)	0-13627-18877-8	
AHB115A ①	4.58m (15ft), 105 Watts	5	5.0kg (11lb)	0-13627-18879-2	
AHB118 ①	5.49m (18ft), 126 Watts	5	3.2kg (7lb)	0-13627-10955-1	
AHB124	7.31m (24ft), 168 Watts	5	3.6kg (8lb)	0-13627-10956-8	
AHB130	9.14m (30ft), 211 Watts	5	4.1kg (9lb)	0-13627-10957-5	
AHB140	12.19m (40ft), 280 Watts	5	5.4kg (12lb)	0-13627-10958-2	
AHB160	18.29m (60ft), 420 Watts	5	6.8kg (15lb)	0-13627-10959-9	
AHB180	24.38m (80ft), 560 Watts	5	9.1kg (20lb)	0-13627-10960-5	
GTXAHB	Starter kit: 2 each of ①'d above	–	8.6kg (19lb)	0-13627-10948-3	
GWJAHB	Jumbo kit: 5 each of ①'d above	–	25.0kg (55lb)	0-13627-10949-0	

① Individual cables are available as part of a kit, see GTXAHB or GWJAHB.