

# UNIPAK, Low Voltage Fixed Capacitor Banks

## 17X23PMURF

UPC:782116058358

### Dimensions:

- Height: 25.3 IN
- Length: 11.1 IN
- Width: 10.131 IN

### Weight:44 LB

**Notes:**Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.

#### Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- Type: UNIPAK
- Amperage Rating: 42A
- Enclosure: NEMA 1, 3R
- Enclosure Material: 14 ga. steel finished w/durable powder coat finish
- Frame Size: B1
- Fuse Type: Three slottedblade type fuses with 200,000 ampere interrupting capacity, Fuses mounted on stand-off bushings or fuse blocks, solderless connectors for easy hookup of incoming line conductors.
- Indicator: Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard
- Phase: Three-phase
- **Product Category:** Low Voltage Fixed Capacitor Banks

#### pe.eaton.com



- Protection: Three fuses, three lights
- Rating: 17.5 kVAR
- Voltage Rating: 240V

# Supporting documents:

- Eatons Volume 3-Power Distribution and Control Assemblies
- Eaton Specification Sheet 17X23PMURF

### **Certifications:**

- CSA Certified
- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.