



Powering Business Worldwide

pe.eaton.com

Definite Purpose Control - Contactor

C25KNE3300A

UPC:782114183762

Dimensions:

- **Height:** 9.11 IN
- **Length:** 7.25 IN
- **Width:** 7.05 IN

Weight:20 LB

Notes:Resitive Load rating per pole

Warranties:

- 1 year

Specifications:

- **Amperage Rating:** 300A
- **Coil:** 110-120 Vac, 50/60 Hz
- **Enclosure:** Open with metal mounting plate
- **Frame Size:** 200 and 300A, three-pole
- **Model:** Contactor
- **Number Of Poles:** Three-pole
- **Terminals:** Box lugs (posidrive setscrew)
- **Type:** Non-reversing

Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [C25KNE3 2D Drawing Xchange](#)
- [C25KNE3 3D Model Xchange](#)
- [C25KNE3AutoCAD 2D Footprint \(mm\)](#)
- [C25KNE3 3D Inventor](#)
- [C25KNE3 2D PDF](#)
- [C25KNE3 AutoCAD 2D Footprint](#)
- [Eaton Specification Sheet - C25KNE3300A](#)

Certifications:

- UL Recognized
- CSA Certified



Product compliance: No Data

© 2016 Eaton. All rights reserved.