



House Panel

HP40SHA

UPC:782116060108

Dimensions:

Height: 40.2 INLength: 30 INWidth: 6.5 IN

Weight: 120 LB

Notes:For 10 kAIC, use BR or BW breakers as secondary main. Confirm security type for individual EUSERC utility requirements. Load conductors can exit the top, bottom, side or back. Secondary breaker not included.

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Amperage Rating: 400A
Bus Material: Aluminum
Bypass: Manual bypass
Enclosure: NEMA 3R
Feed Type: Underground
Interrupt Rating: 22 kAIC

Line: Lug landings for compression, lugs not included

Main Circuit Breaker: CSR2200Mounting: Surface mounting

• Number Of Sockets: 1

• Secondary Circuit Breaker: BRH/BWH

• Security: Ring

Used With: Type BR breakersVoltage Rating: 120/240V



Supporting documents:

- Eatons Volume 1-Residential and Light Commercial
- Eaton Specification Sheet HP40SHA

Certifications:

• UL Listed

Product compliance:

• EUSERC Approved

© 0040 Fatar. All rights recovered

© 2016 Eaton. All rights reserved.