



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## S811+ Soft Starter with Digital Interface Module

**S811+R10N3S**

**UPC:**786685558936

### Dimensions:

- **Height:** 7.92 IN
- **Length:** 6.64 IN
- **Width:** 4.38 IN

**Weight:**10.5 LB

**Notes:**All units require a 24 Vdc power supply found on catalog Page V6-T1-85, or equivalent., S811+T\_, S811+U\_ and S811+V\_ units require lug kits, S811+U50\_ unit does not have IEC certification.

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Amperage Rating:** 1000A
- **Communication:** Modbus RTU
- **Display Material:** LCD
- **Frame Size:** R-frame
- **Frequency Rating:** 47-63 Hz
- **Maximum Ac Current:** 240 Vac
- **Maximum Dc Current:** 120 Vdc
- **Module Interface:** Digital interface module
- **Nema Rating:** NEMA Type 0
- **Number Of Conductors:** 2-Jan
- **Number Of Poles:** Three-pole
- **Operating Temperature:** -30° to 50°C
- **Operating Voltage:** 200-600V
- **Power Supply:** 24V
- **Size:** NEMA 0



- **Type:** Soft starter
- **Used With:** Three-phase motors
- **Wire Size:** #22-14 AWG

**Supporting documents:**

- [Product Datasheet - S811+R10N3S](#)

**Certifications:**

- CSA file No. 3211-06
- UL Recognized
- EN 60947-4-2
- IEC 60947-4-2
- UL Listed
- CSA Certified for Elevator Duty

**Product compliance:**

- CE Marked