



Powering Business Worldwide

pe.eaton.com

DOE 2016 Efficient Transformer, Dry-type, Ventilated, Three- phase

V48M22T1216

UPC:786680167768

Dimensions:

- **Height:** 51 IN
- **Length:** 31.5 IN
- **Width:** 34.5 IN

Weight:1.1 LB

Notes:10 CFR Part 431 (2016) Efficient

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Aluminum
- **Efficiency:** DOE2016
- **Enclosure:** NEMA 2
- **Frame:** 943
- **Frequency Rating:** 60 Hz
- **Insulation:** 220C
- **Kva Rating:** 112.5 kVA
- **Material:** Al windings
- **Phase:** Three-phase
- **Primary Voltage:** 480V Delta
- **Secondary Voltage:** 240V Delta with 120V Itg tap
- **Sound Level:** NEMA ST-20
- **Tap Size:** +2,-4 at 2.5%
- **Temperature Rating:** 150°C rise
- **Weathershield:** WS60
- **Wiring Connection:** 280B



Supporting documents:

- [Eaton Specification Sheet - V48M22T1216](#)

Certifications:

- UL Listed (when used with Eaton socket)

Product compliance:

- DOE2016 Efficient