


16092 - F17T8XLSPX65ECO

GE Ecolux® Starcoat® T8

• Passes TCLP, which can lower disposal costs.







CAUTIONS & WARNINGS

Caution


- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

Warning


- Risk of Electric Shock
- Turn power off before inspection, installation or removal.

GRAPHS & CHARTS

Graphs_Lumen Maintenance



Graphs_Lamp Mortality



GENERAL CHARACTERISTICS

Lamp Type

Bulb Base Rated Life Rated Life (instant start) @ Time Rated Life (rapid start) @ Time

Bulb Material Starting Temperature (MIN) LEED-EB MR Credit

Additional Info Primary Application

PHOTOMETRIC CHARACTERISTICS

Initial Lumens1Mean Lumens1Nominal Initial Lumens per Watt7Color Temperature6Color Rendering Index (CRI)7S/P Ratio (Scotopic/Photopic2Ratio)2

Full Wattage **TERISTICS** 1250.0 1125.0 tt 73 6500.0 K 78.0 2.3

Linear

12.0 h Soda lime

10.0 °C

lumen hour

TCLP compliant

40000.0 hrs

18000 h @ 3 h

24000 h @ 12 h

40000.0 @ 3.0/45000.0 @

66 picograms Hg per mean

T8

Linear Fluorescent - Straight

Medium Bi-Pin (G13)

ELECTRICAL CHARACTERISTICS

Wattage 17.0 Voltage 70.0 Open Circuit Voltage (rapid 285.0 V start) (MAX) Open Circuit Voltage (rapid 210 V @ 10 °C start) Min @ Temperature Cathode Resistance Ratio - Rh/ 4.25 Rc (MIN) Cathode Resistance Ratio - Rh/ 6.5 Rc (MAX) Current Crest Factor (MAX) 1.7

DIMENSIONS

| Maximum Overall Length (MOL) | 23.7800 in(604.0 mm) |
|---------------------------------|----------------------|
| Minimum Overall Length | 23.6700 in(601.2 mm) |
| Nominal Length | 24.000 in(609.6 mm) |
| Bulb Diameter (DIA) (MIN) | 0.940 in(23.9 mm) |
| Bulb Diameter (DIA) (MAX) | 1.100 in(27.9 mm) |
| Bulb Diameter (DIA) | 1.000 in(25.4 mm) |
| Max Base Face to Base Face | 23.220 in(589.8 mm) |
| (A) | |
| Face to End of Opposing Pin | 23.400 in(594.4 mm) |
| (B) (MIN) | |
| Face to End of Opposing Pin | 23.500 in(596.9 mm) |
| (B) (MAX) | |
| End of Base Pin to End of | 23.670 in(601.2 mm) |
| Opposite Pin End (C) | |
| | |

PRODUCT INFORMATION

| Product Code | 16092 |
|----------------------------|-----------------|
| Description | F17T8XLSPX65ECO |
| ANSI Code | 1001-1 |
| Standard Package | Case |
| Standard Package GTIN | 10043168160923 |
| Standard Package Quantity | 24 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard | 24 |
| Package | |
| UPC | 043168160926 |