



GE
Lighting

65706 - Remote 2ft LED Plastic Tubes

LED9T8/2/835

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is operated by a GE Lighttech™ driver.
- ☞ 66% longer life than LFL (50,000 vs. 30,000 hours)
- ☞ Instant on light
- ☞ NSF Rated for food application (shatter resistant)
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed
- ☞ DLC Listed

Product Photo



GENERAL CHARACTERISTICS

Product Technology	LED
Rated Life (Hours)	50000 h
LED Tube Type	Plastic
Environmental Rating	LED_Tube_Plastic
10 Digit U	4316865706
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Sleeve
Estimated Energy Cost per Year	1.08
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Rated Beam Spread	8 W
Initial Lumens-nominal	1 lm
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	65706
Description	LED9T8/2/835
Alternative Unit Of Measure	EACH
Standard Package Quantity	20
Ean UPC	043168657068
Standard Package GTIN	00043168657068
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
Sales Unit	Each
UCC	043168657068
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168657068
Standard Package GTIN	10043168657065
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	043168657068

DIMENSIONS

Bulb Max Overall Length-MOL	24.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Drive Current	45.7
Energy Efficiency Class	yr
Voltage <Nom>	120 V
Rated power (Watts)	8 W

CAUTIONS & WARNINGS

Caution

Risk of electric shock

Suitable for damp locations

Not intended for use with emergency exit fixtures or emergency exit lights