


# 23731 - Q500T3/CL

GE Quartzline® T2.5 - Stage & Studio







## **CAUTIONS & WARNINGS**

### Caution

- · Lamp may shatter and cause injury if broken
- Dispose of lamp in a closed container.
- Do not use lamp if outer glass is scratched or broken.

#### Warning

- Lamp emits UV radiation which may cause eye/skin injury. RG-3
- Avoid exposure of eyes and skin to unshielded lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Burn
- Allow lamp to cool before handling.
- Turn power off before installing lamp.
- Risk of Fire
- Fire Hazard! Do not use in Torchieres or other indoor residential fixtures.
- Keep combustible materials away from lamp.
- Use in enclosed fixture rated for this product.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
- Do not exceed 110% of rated voltage.
- Do not touch glass with bare hands.
- Do not use lamp if outer glass is scratched or broken.
- Operate lamp only in specified position -- see instructions.
- Use eye protection when handling lamp.
- Use in enclosed fixture rated for this product.

# **GENERAL CHARACTERISTICS**

Lamp Type Bulb Base Filament

Filament Bulb Finish Rated Life Primary Application Halogen - Double-Ended T2.5 Recessed Single Contact (R7s) C-8 Clear 2000.0 hrs Stage & Studio

## PHOTOMETRIC CHARACTERISTICS

Initial Lumens11100.0Color Temperature3000.0 KNominal Initial Lumens per Watt22

ELECTRICAL CHARACTERISTICS

Wattage500.0Voltage120.0Burn PositionHorizontal

## DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) Light Center Length (LCL) 4.6880 in(119.1 mm) 0.312 in(7.9 mm)

2.250 in(57.2 mm)

PRODUCT INFORMATION Product Code

Description ANSI Code Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC 23731 Q500T3/CL FCL Case 10043168237311 12 Unit 1 12

043168237314