

156-00594

Article Number: 156-00594

Omega Clip Tie, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pk



## Base Data

Local Order Number 156-00594

Type T50ROC2

Color Black (BK)

**Features and Benefits** Omega Clips secure cables to tubular frame rails. The UV stabilized cable tie is fastened to the tubular frame rail and the solar cable snaps into the clip. The cable can be removed from the clip and reinstalled without additional fasteners.

Fixation Method (FF) Omega Clips

Identification Plate Position none

Short Description Omega Clip Tie, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pk

## Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 7.9 "

Length L (metric) 200 mm

Attaches to Diameter (imperial) 0.26 " - 0.3 "

Width W (imperial) 0.18 "

Width W (metric) 4.6 mm

Bundle Diameter min (imperial) 1.8 "

Bundle Diameter min (metric) 6.5 mm

Bundle Diameter max (imperial) 1.8 "

Bundle Diameter max (metric) 45 mm

Attaches to Diameter (metric) 6.5 - 7.5 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 500

## Material and Specifications

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
Polyamide 6.6 UV-stabilized (PA66UV)

**Material Shortcut** PA66HIRHS  
PA66UV

**Material Cable Tie** Polyamide 6.6 UV-stabilized (PA66UV)

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)  
-40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes