

181-00228



Article Number: 181-00228

High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, Gray, 120ft/Carton



## Base Data

**Local Order Number** 181-00228  
**Type** SLHD2.5X3  
**Color** Gray (GY)

**Features and Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wall, wiring duct features narrow fingers, equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 2.5" X 3", Non- Adhesive, PVC, Gray, 120ft/Carton

## Product Dimensions

**Length L (imperial)** 6.0 ft  
**Length L (metric)** 1.83 m  
**Width W (imperial)** 2.5 "  
**Width W (metric)** 63.5 mm  
**Width W2 (imperial)** 2.5 "  
**Width W2 (metric)** 63.5 mm  
**Width W3 (imperial)** 0.16 "  
**Width W3 (metric)** 4.1 mm  
**Width W4 (imperial)** 0.4 "  
**Width W4 (metric)** 10.16 mm  
**Width W5 (imperial)** 2.6 "  
**Width W5 (metric)** 66.04 mm  
**Width W6 (imperial)** 0.75 "  
**Width W6 (metric)** 19.05 mm  
**Height H (imperial)** 3.0 "  
**Height H (metric)** 76.2 mm

## Logistics and Packaging

**Quantity per** carton  
**Package Quantity (imperial)** 120  
**Package Quantity** 36.6 m

## Material and Specifications

---

<b>Material</b>	Polyvinylchloride (PVC)
<b>Material Shortcut</b>	PVC
<b>Flammability</b>	self-extinguishing
<b>Operating Temperature</b>	+122 °F (+50 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Recognized (US)</b>	Yes