

181-11005



**Article Number:** 181-11005

**Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 120ft/Carton**



## Base Data

**Local Order Number** 181-11005

**Type** SD1X1

**Color** White (WH)

**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, 1" X 1", Non-Adhesive, PVC, White, 120ft/Carton

## Product Dimensions

**Length L (imperial)** 6.0 ft

**Length L (metric)** 1.83 m

**Width W (imperial)** 1.0 "

**Width W (metric)** 25.4 mm

**Width W2 (imperial)** 1.0 "

**Width W2 (metric)** 25.4 mm

**Height H (imperial)** 1.05 "

**Height H (metric)** 26.7 mm

**Mounting Hole Centers (imperial)** 4.0 "

**Mounting Hole Centers (metric)** 101.6 mm

## Logistics and Packaging

**Quantity per** carton

**Package Quantity (imperial)** 120 ft

**Package Quantity** 120

**Carton Quantity** 120

## Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**CSA Certified** Yes

<b>Flammability</b>	self-extinguishing
<b>Operating Temperature</b>	+122 °F (+50 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL CSA
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No
<b>UL Recognized (US)</b>	Yes