HellermannTyton

181-34001



Article Number: 181-34001

Solid Wall Wiring Duct, 3" X 4", Non-Adhesive, PVC, White, 120ft/Carton

RoHS

Base Data

Local Order Number 181-34001

Type SD3X4

Color White (WH)

Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during

stallation.

· Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily

snap on and off. (Covers to be purchased separately)

Product Description HellemannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring

duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6

foot lengths.

Short Description Solid Wall Wiring Duct, 3" X4", Non-Adhesive, PVC, White, 120ft/Carton

Product Dimensions

Length L (imperial) 6.0 ft

Length L (metric) 1.83 m

Width W (imperial) 3.0 "

Width W (metric) 76.2 mm

Width W2 (imperial) 3.0 "

Width W2 (metric) 76.2 mm

Width W6 (imperial) 1.0 "

Width W6 (metric) 25.4 mm

Height H (imperial) 4.06 "

Height H (metric) 103.1 mm

Mounting Hole Centers (imperial) 4.0 "

Mounting Hole Centers (metric) 101.6 mm

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 120 ft

Package Quantity 36.6 m

Carton Quantity 120

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

CSA Certified Yes

Flammability self-extinguishing

Operating Temperature +122 °F (+50 °C)

ROHS Conformity Yes

Certification / Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes