

333-41504

Article Number: 333-41504

Heat Shrink Tubing, Bulk Reel, 3:1, 3/4", 19.1/6.0 dia., Polyolefin, Black, 200 ft/reel

HellermannTyton



Base Data

Local Order Number 333-41504

Type TFN31-18/6 BK

Color Black (BK)

- Features and Benefits**
- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
 - Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
 - Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
 - Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

Product Description TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

Shrink Ratio 3:1

Variant Thin-Wall

Short Description Heat Shrink Tubing, Bulk Reel, 3:1, 3/4", 19.1/6.0 dia., Polyolefin, Black, 200 ft/reel

With inner glue (Yes/No) ETIM No

Product Dimensions

Length L (imperial) 200.0 ft

Length L (metric) 61.0 m

Wall Thickness WT (imperial) 0.035 "

Wall Thickness WT (metric) .90 mm

Recovered Diameter D (metric) 6.0 mm

Recovered Diameter D (imperial) 0.375 "

Supplied Diameter D (imperial) 0.75 "

Supplied Diameter D (metric) 19.1 mm

Logistics and Packaging

Quantity per reel

Package Quantity (imperial) 200

Trade Size 3/4

Material and Specifications

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Dielectric Strength (metric) 20 kV/mm

Elongation at break	600%
Flammability	UL224 VW-1
Halogenfree	No
Shrink Temperature	+212 °F (+100 °C)
Operating Temperature	-67 °F to +275 °F (-55 °C to +135 °C)
ROHS Conformity	Yes
Certification / Specification	UL224 125 °C 600V VW-1 CSA
Tensile Strength (MPa)	14 MPa
UL Recognized (US)	Yes
Volume Resistance (Ohm cm)	10 ¹¹ Ω cm