

596-00252

Article Number: 596-00252

Solar Label, AC Module Printable Solar Label, 4.0" X 2.0", Vinyl, Red, 50/RL



Base Data

Local Order Number 596-00252

Type AC2011

Color Red (RD)

Features and Benefits

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Color of Print White (WH)

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description

4" X2" White text on red background that reads as: "NOMINAL AC VOLTAGE;NOMINAL OPERATING AC FREQUENCY;MAXIMUM AC POWER;MAXIMUM AC CURRENT;MAXIMUM OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Short Description Solar Label, AC Module Printable Solar Label, 4.0" X2.0", Vinyl, Red, 50/RL

Product Dimensions

Width W (imperial) 4.0 "

Width W (metric) 101.6 mm

Height H (imperial) 2.0 "

Height H (metric) 50.8 mm

Logistics and Packaging

Quantity per roll

Package Quantity (imperial) 50

Package Quantity 50

Material and Specifications

Material Vinyl

Material Shortcut Vinyl

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -40 °F to +180 °F (-40 °C to +82 °C)

Halogenfree Yes

Operating Temperature -40 °F to +302 °F (-40 °C to +150 °C)

Recommended Ribbon Type TT822OUT

ROHS Conformity Yes

UL Recognized (US) Yes