



DCT110HIRC2



Article Number: 115-00033

Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 100/pkg

 **RoHS**

Base Data

Local Order Number	DCT110HIRC2
Type	DCT11
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Provides dual separation between bundles to prevent chaffing and abrasion.• 150 lb. tensile strength ensures enough strength for heavy duty applications.• Straps are releasable for increased serviceability.
Product Description	HellermannTyton's dual clamp ties are designed to provide parallel separation between hoses, wires, cables and tubing, protecting them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of tracks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.
Fixation Method (FF)	Weld Stud Fixing
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	150.0 lbs
Length L (imperial)	19.0 "
Length L (metric)	489.0 mm
Width W (imperial)	0.5 "
Width W (metric)	12.8 mm
Width W2 (imperial)	0.7 "
Width W2 (metric)	19.7 mm
Height H (imperial)	0.8 "
Height H (metric)	19.1 mm
Bundle Diameter min (imperial)	0.12 "
Bundle Diameter min (metric)	3.0 mm
Bundle Diameter max (imperial)	2.3 "
Bundle Diameter max (metric)	58.0 mm
Mounting Hole Diameter D (imperial)	0.2 "
Mounting Hole Diameter D (metric)	6.2 mm
Thickness T (imperial)	0.055 "
Thickness T (Metric)	1.4 mm

Stud Size (Imperial)	0.25 "
Stud Size (Metric)	6.35 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	500
Weight (Metric)	2.2 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes