

HDM250HIRC2



Article Number: 151-00437

Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 100/pkg



Base Data

| | |
|------------------------------|---|
| Local Order Number | HDM250HIRC2 |
| Type | HDM25 |
| Color | Black (BK) |
| Features and Benefits | <ul style="list-style-type: none"> • Mount and tie combination makes it easy to service bundles in the field. • Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. • Eliminates the needs for multiple sized fix diameter clamps. |
| Product Description | This mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process. |
| Fixation Method (FF) | Screw Mounting and Rivet |
| Short Description | Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 100/pkg |

Product Dimensions

| | |
|--|---------|
| Length L (imperial) | 1.4 " |
| Length L (metric) | 35.8 mm |
| Width W (imperial) | 0.75 " |
| Width W (metric) | 19.0 mm |
| Cable Tie Width Max (imperial) | 0.5 " |
| Cable Tie Width max. (metric) | 12.7 mm |
| Width W2 (imperial) | 0.52 " |
| Width W2 (metric) | 13.3 mm |
| Height H (imperial) | 0.66 " |
| Height H (metric) | 16.7 mm |
| Height H2 (imperial) | 0.31 " |
| Height H2 (metric) | 8.0 mm |
| Mounting Hole Diameter D (imperial) | 0.25 " |
| Mounting Hole Diameter D (metric) | 6.2 mm |

Logistics and Packaging

| | |
|-------------------------|------|
| Quantity per | bag |
| Package Quantity | 100 |
| Carton Quantity | 2500 |

Material and Specifications

| | |
|--------------------------|--|
| Material | Polyamide 6.6 high impact modified (PA66HIR) |
| Material Shortcut | PA66HIRHSUV |

| | |
|--------------------------------|---------------------------------------|
| Flammability | UL94 HB |
| Maximum Torque (kgf-cm) | 132.5 kgf-cm |
| Maximum Torque (lbf-ft) | 9.583 lbf-ft |
| Operating Temperature | -40 °F to +230 °F (-40 °C to +110 °C) |
| ROHS Conformity | Yes |