

T50IDH0C2

Article Number: 117-05362

Double Head Tie, 12" Long, 50lb Tensile Strength, PA66, Black, 100/pkg



Base Data

Local Order Number T50IDH0C2

Type T50IDH

Color Black (BK)

- Features and Benefits**
- The tie contains a dual locking design to secure two bundles at once.
 - Head design can also provide spacing between parallel bundles.
 - Bent tail allows for quick insertion into head.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Number of bundles 2

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Double Head Tie, 12" Long, 50lb Tensile Strength, PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 12.0 "

Length L (metric) 305.0 mm

Bundle Diameter 2nd Loop max (imperial) 1.5 "

Width W (imperial) 0.19 "

Width W (metric) 4.7 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.6 mm

Bundle Diameter max (imperial) 1.5 "

Bundle Diameter max (metric) 38.1 mm

Bundle Diameter 1st Loop max (imperial) 3.0 "

Bundle Diameter 1st Loop max (metric) 76.2 mm

Bundle Diameter 2nd Loop max (metric) 38.1 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

Flammability UL94 V2

Halogenfree Yes

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes