

TAG6T1-100B

Article Number: 596-00016

Thermal Transfer Self-Laminating Label, 2.0" X 1.0" X 3.75", 1 Across, Vinyl, White, 1000/RL



Base Data

Local Order Number TAG6T1-100B

Type TAG6T1

Color White (WH)

- Features and Benefits**
- Clear laminate provides excellent abrasion protection and chemical resistance.
 - Flexible material bends around small gauge wires and tight bends.
 - Labels are UL recognized and include a strong acrylic adhesive for indoor and outdoor use.
 - Standard 3" core can be used with HellermannTyton thermal transfer printers or most standard brands.

Color Marking Field White (WH)

Product Description HellermannTyton self-laminating thermal transfer printer labels are made of a flexible vinyl film with a white printable surface that easily conforms to wires. These labels include a clear "tail" that laminates printed text when applied. Labels are UL recognized for indoor and outdoor use and feature a strong acrylic adhesive designed to bond to both large and small diameter wires.

For Wire Type 50 Pair Copper

Short Description Thermal Transfer Self-Laminating Label, 2.0" X 1.0" X 3.75", 1 Across, Vinyl, White, 1000/RL

Product Dimensions

Length L (imperial) 3.75 "

Length L (metric) 95.25 mm

Width W (imperial) 2.0 "

Width W (metric) 50.8 mm

Height H (imperial) 1.5 "

Height H (metric) 38.1 mm

Height H2 (imperial) 3.75 "

Height H2 (metric) 95.25 mm

Bundle Diameter min (imperial) 0.39 "

Bundle Diameter min (metric) 10.0 mm

Bundle Diameter max (imperial) 0.87 "

Bundle Diameter max (metric) 22.2 mm

Horizontal Repeat HR (metric) 50.8 mm

Horizontal Repeat HR (imperial) 2.0 "

Print Method Thermal Transfer

Thickness T (Metric) 25 µm

Vertical Repeat VR (imperial) 4.0 "

Vertical Repeat VR (metric) 101.6 mm

Width of Liner WL (imperial) 2.2 "

Width of Liner WL (metric) 55.88 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	1000
Package Quantity	1000
Carton Quantity	1000
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.1 kg

Material and Specifications

Material	Type 100, self laminating Vinyl, white (WH)
Material Shortcut	100B
Adhesive	Acrylic
Shortcut Adhesive	Acryl
Adhesive Operating Temperature	-40 °F to +194 °F (-40 °C to +90 °C)
Operating Temperature	-40 °F to +194 °F (-40 °C to +90 °C)
ROHS Conformity	Yes
Certification / Specification	UL-Recognized