HellermannTyton

TSRP1W-6A

Article Number: 250-61602

RoHS

One Piece Low Voltage Raceway, 3/4", 6.0 ft Long, PVC, White, 120ft/Carton

HellermannTyton

Base Data

Local Order Number	TSRP1W-6A
Туре	TSRP1-6A
Color	White (WH)
Features and Benefits	• Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables.
	 An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration.
	 Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes.
	Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Product Description	HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent
	data transmission performance of Category 6A, 6 and 5e communications systems.
Short Description	One Piece Low Voltage Raceway, 3/4", 6.0 ft Long, PVC, White, 120ft/Carton

Product Dimensions

Length L (Imperial)	6.0 ft
Length L (Metric)	1.83 m
Width W (Imperial)	0.75 "
Width W (Metric)	19.05 mm
Height H (Imperial)	0.5 "
Height H (Metric)	12.7 mm
Height H2 (Metric)	12.7 mm

Logistics and Packaging

Quantity Per	carton
Package Quantity	120.0 ft
Package Quantity (Metric)	36.6 m
Carton Quantity	120.0 ft

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
ROHS Compliant	Yes
UL Listed (US and Canada)	No
UL Listed (US)	No

© HellermannTyton 2015