

T822K1018/U

THERMOSTAT – LOW VOLTAGE / 24 V

COLOR

- white

VOLTAGE

- 1.2 A @ 24 Vac

CONTROL

- two-wire connection
- all or nothing (on/off) @ 24 Vac
- compatible with all RE, RM and R841 model relays
- temperature in degrees Fahrenheit

TEMPERATURE RANGE

- 50 to 86 °F

WARRANTY

- one year



PRODUCT	DESCRIPTION	PRICE
T822K1018/U	LOW VOLTAGE THERMOSTAT (24 V)	50.50

Dimensions: 2.83 in. x 4.75 in. x 1.46 in.



T87K1007/U

THERMOSTAT – LOW VOLTAGE / 24 V

COLOR

- white

VOLTAGE

- 1 A @ 24 Vac

CONTROL

- two-wire connection
- all or nothing (on/off) @ 24 Vac
- compatible with all RE, RM and R841 model relays
- temperature in degrees Fahrenheit

TEMPERATURE RANGE

- 50 to 86 °F

WARRANTY

- one year



PRODUCT	DESCRIPTION	PRICE
T87K1007/U	LOW VOLTAGE THERMOSTAT (24 V)	63.50

Dimensions: 3 11/16 in. diameter x 1 3/4 in.



°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.

FC_T822K-T87K_US_1151018