

TYPE ILC-15H

Features

- Lightweight - only 14.1 lbs
- Accepts P or U dies with adaptor
- Hot stick attachment point
- Equipped with 3/8" male screw coupler
- Zinc plated head

Benefits

- Easy to hold, less tiring for numerous crimps
- Versatility and efficiency. Use your current dies with this tool
- Offers the option of performing line maintenance when properly protected
- For use with standard industry hoses
- Excellent corrosion resistance for long tool life

Specifications

Force developed: 15 Tons
 Operating pressure: 10,000 PSI
 Weight (with case): 14.1 lbs.
 Overall length: 15"
 Maximum width: 3"
 Conductor Range: 1000kcmil-#8 AL or CU



For Use with*	
Aluminum Connectors	Copper Connectors
CPM Series	CLN4, CLN9, CLND, CSLT, CLWU
ACM Series	CLNF, CLNN, CLNS,
ACO Series	CLNU, CLW4, CLW9,
ACO-90 Series	CLWD, CLWF, CLWN,
ACL, ACN 1000kcmil-8	CLWS, CSN4, CSN9,
2ACL, 2ACN 1000kcmil-1/0	CSND, CSNF, CSNN,
AS 1000kcmil-8	CSNS, CSW4, CSW9,
HT Series	CSWD, CSWF, CSWN,
AH Series	CSWS thru 1000kcmil
IACL Series	
2IACL Series	
Series: ALNS, ALND, ASN,	
ALNN thru 1000 kcmil	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

*See page 405 for required compression dies

Note: If using "P" dies, an ILD-PADP must be used.

If using "U" dies, an ILD-UADP must be used.

Additional Requirements:

- Hose
- Pump
- Adaptor required with all dies