

IG1300-2T-1C3

- Type 2 SPD applications
- 12 gauge wire
- Provides protection for 2 telephone lines (Analog phone line, modem, or DSL) and 1 coax line (cable TV, cable Internet or Satellite TV)
- Type 3R outdoor rainproof enclosure for indoor/outdoor installations (9.38" H x 5.25" W x 4" D)
- 6 modes of surge protection:
L1-N, L2-N, L1-G, L2-G, N-G, L1-L2
- 5-year product warranty
- \$10,000 connected equipment warranty for 5 years on appliances and electronics



D.

IG1300-4T-2C3

- Type 2 SPD applications
- 12 gauge wire
- Provides protection for 4 telephone lines (Analog phone line, modem, or DSL) and 2 coax lines (cable TV, cable Internet or Satellite TV)
- Type 3R outdoor rainproof enclosure for indoor/outdoor installations (9.38" H x 5.25" W x 4" D)
- 6 modes of surge protection:
L1-N, L2-N, L1-G, L2-G, N-G, L1-L2
- 5-year product warranty
- \$10,000 connected equipment warranty for 5 years on appliances and electronics



E.

Model #	Service Voltage	No. of Leads	Lead Length	Wiring Config.	Nominal Discharge Current	MCOV*	SCCR**	Voltage Protection Rating (VPR)				
								L-N/G	L-N	L-G	N-G	L-L
D. IG1300-2T-1C3	120, 240 VAC	4	24"	L1, L2, N, G	20 kA	150 L-N, N-G†	50 kA	700	1200	700	1200	
E. IG1300-4T-1C3	120, 240 VAC	4	24"	L1, L2, N, G	20 kA	300 L-L, L-G†	50 kA	700	1200	700	1200	

*MCOV Maximum Continuous Operating Voltage

**SCCR Short Circuit Current Rating

†Applies to all models

Flushmount Kit

- For IG1200RC3, IG1240RC3 and IG3240RC3
- Includes mounting plate, screws and mounting bracket
- Easy to use

Model #	H x W
F. IG1240FMP33	7" x 7.5"
G. IG3240FMP33	7" x 7.5"



F.



G.