

# KICHLER®


PROJECT:
TYPE:
ORDERING # :
COMMENTS:

## LED 6" Dome Path Light








## FEATURES

- A popular look has a new addition with a smaller 6" shade and is available in LED.
- Coordinates with 15810 & 15811 LED Domed Roof series.
- Cast Aluminum or Cast Brass Housing.
- 4 W / 5.8 VA, Integrated LEDs and Driver, 2950K (-150/+175), High CRI.
- 9V - 15V AC/DC
- 30" of usable #18-2, SPT-1-W leads. Cable connector supplied.
- 8" In-ground stake



## ORDERING INFORMATION

EXAMPLE: 15870AZT (Product # & Finish)

PRODUCT	FINISH	WATTAGE	LIGHT SOURCE	WIRING	MOUNTING ACCESSORIES (INCLUDED)	OPTIONS & ACCESSORIES																				
<b>15870</b> Dimensions: 6" W x 21.25" L	<b>Cast Aluminum</b> <b>AZT</b> - Textured Architectural Bronze™	4 W / 5.8 VA  <b>Note:</b> Not for use with electronic transformers.	Integrated LEDs and Driver 2950K (-150 / +175) High CRI	30" of usable #18-2, SPT-1-W leads.  Cable connector supplied.	8" In-ground stake	<b>15601AZT</b> - Cast Aluminum Surface Mounting Flange w/ Bronze Finish, Neoprene Gasket For Watertight Seal																				
						<b>15601BKT</b> - Cast Aluminum Surface Mounting Flange w/ Black Finish, Neoprene Gasket For Watertight Seal																				
	<b>BE</b> - Beach						<b>15601BBR</b> - Cast Brass Surface Mounting Flange, Neoprene Gasket For Watertight Seal																			
	<b>BKT</b> - Textured Black																									
<b>Cast Brass</b> <b>BBR</b> - Bronzed Brass						<b>Flange For Tree / Surface Mounting</b> <b>15607AZT</b> - Textured Bronze Finish <b>15607BKT</b> - Textured Black Finish <b>15607BBR</b> - Bronzed Brass Finish																				
		Fixture Photometric (fc)																								
		<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td> <td>1'</td> <td>2'</td> <td>3'</td> <td>4'</td> <td>5'</td> <td>6'</td> <td>7'</td> <td>8'</td> </tr> <tr> <td>Footcandles</td> <td>6.11</td> <td>5.71</td> <td>3.97</td> <td>2.55</td> <td>1.64</td> <td>0.90</td> <td>0.50</td> <td>0.40</td> <td>0.31</td> </tr> </table>		Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	6.11	5.71	3.97	2.55	1.64	0.90	0.50	0.40	0.31			
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																	
Footcandles	6.11	5.71	3.97	2.55	1.64	0.90	0.50	0.40	0.31																	



## NOTES

For Warranty Information, please visit [www.landscapelighting.com](http://www.landscapelighting.com)

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.