



RIGID • IMC

Three piece Couplings for Rigid Conduit • IMC Malleable Iron

Features

- Heavy duty casting
- Concrete tight
- Direct burial without tape
- Couples conduits when conduit cannot be turned
- RoHS compliant

Standard Materials


Malleable iron

Standard Finish

Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. W-F-408E
- NEMA: FB-1
- UL Listed File # E207875



Three Piece Coupling



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	INNER PACK	MASTER PACK	WEIGHT PER C
EC50KON	1/2"	1.313	1.375	1.375	10	100	26.1
EC75KON	3/4"	1.563	1.563	1.563	5	50	36.6
EC100KON	1"	1.625	1.875	1.875	5	50	55.3
EC125KON	1-1/4"	2.125	2.375	2.375	5	25	110.5
EC150KON	1-1/2"	2.375	2.813	2.813	5	25	171.9
EC200KON	2"	2.625	3.313	3.313	2	10	202.6
EC250KON	2-1/2"	3.125	4.063	4.063	2	10	327.4
EC300KON	3"	3.188	4.688	4.688	—	5	442.0
EC350KON	3-1/2"	3.563	5.063	5.063	—	1	607.8
EC400KON	4"	4.000	5.750	5.750	—	1	718.3
EC500KON	5"	4.000	7.250	7.250	—	1	1050.0
EC600KON	6"	3.875	8.313	8.313	—	1	1250.0