






UPC Code: 07847780776

Country Of Origin: United States

**NEMA:** L12-30R



# 2683

#### **Brand Features**

Leviton's industry leading locking devices, such as our Black &White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

#### **Item Description**

30 Amp, 480 Volt 3-Phase, NEMA L12-30R, 3P, 3W, Locking Connector, Industrial Grade, Non-Grounding - BLACK-WHITE

#### **Technical Information**

AC Horsepower Ratings
At Rated Voltage: 10 HP

Electrical Specifications

Grounding: Non-Grounding

Amperage: 30 A Voltage: 480 VAC

Pole: 3 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rica: May 200 after 250

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Phase: 3-Phase

**Environmental Specifications** 

Flammability: Rated HB or better UL94 Operating Temperature: -40°C to 60°C

**Environment:** Dry Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Wire Module: Nylon Cord-Clamp: Nylon Clamp Insert: Nylon

Blades/Contacts: Solid Brass Terminal Screws: Brass

Assembly Screws: Steel, Zinc Plated

Color: Black-White

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

**Terminal Accom.:** 18-10 AWG **Product ID:** Ratings are permanently

marked on device

Cord Range: .385 - .930 Wire Gauge: 16-8 AWG

**Product Features** 

Cord Range: .385 - .930

NEMA: L12-30R Color: Black-White

**Device Type:** Locking Connector

Brand: Black and White

Standards and Certifications **NEMA:** WD-6

**ANSI:** C-73


UL498: File E13393

**UL Fed Spec WC-596:** File E13393 **CSA C22.2 No. 42:** File LR-406


**NOM**: 057

Warranty: Lifetime Warranty

# **Dimensional Diagram**



# Wiring Diagram



## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

