



515PV-LIT

Brand Features

Leviton offers a large selection of 15, 20, 30 and 50 Amp Commercial Grade Straight Blade Plugs and Connectors, available in a wide variety of features. These rugged performers are moisture, chemical and abuse-resistant, And they're ideal for indoor and outdoor use. Our EPTR rubber-backed plugs and connectors stand up to rough use, protecting against dirt and moisture. The deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.

Item Description

15 Amp, 125 Volt, NEMA 5-15P, 2Pole, 3Wire, Plug, Straight Blade - LIGHTED

Technical Information

Electrical Specifications

Amperage: 15 A
Dielectric Voltage: Withstands 2000V per UL498
Grounding: Grounding
Pole: 2
Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current
Voltage: 125 VAC
Wire: 3

Environmental Specifications

Flammability: Rated V-2 per UL 94
Operating Temperature: -40°C to 60°C

Material Specifications

Assembly Screws: Steel, Zinc Plated
Blades/Contacts: Brass
Body Material: PVC

Mechanical Specifications

Product ID: Ratings and NEMA I.D. permanently marked on device
Terminal Accom.: 18-12 AWG
Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color: Yellow/Transparent
Cord Range: .245 - .655
Feature: Power Indication
NEMA: 5-15P

Standards and Certifications

ANSI: C-73
CSA C22.2 No. 42: File LR-406
NEMA: WD-6
NOM: 057
UL498: File E13393
Warranty: 2-Year Limited

Color: N/A Yellow/Transparent

UPC Code: 07847767485

Country Of Origin: Mexico

NEMA:
5-15P



Features and Benefits

- Ideal for replacement of plugs on tools, appliances and extension cords
- Green light indicates power is flowing through to the cord
- Accepts AWG SJ 16/3
- NEMA 5-15
- cULus, NOM
- Rugged PVC plug and connector (515PV/515CV) resists moisture and chemicals
- Unique dimpled body provides a secure hinge grip
- Built-in cord grip adjusts automatically for use with 18-12 AWG.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

