



UPC Code: 07847762512

Country Of Origin: Mexico

52120-7MS

Brand Features

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Item Description

120/208VAC 3-Phase WYE, 7-Mode, Type 2 Panel Mounted Surge Protective Device with Integral Disconnect Switch and Replaceable Surge Modules: 120-7M3 (3) & 8120-GN (1)

Technical Information

Electrical Specifications

Voltage Configuration: 120/208 V, 3-Phase WYE

Frequency: 50/60Hz

Surge Technology: 40mm MOV Design

Environmental Specifications

Enclosure: Type 13

Operating Temperature: -4°F to 104°F (-20°C to -40°C)

Storage Temperature: -4°F to 185°F (-20°C to 85°C)

Flammability: Rated V-2 per UL 94

Relative Humidity: 5% to 95% non-condensing

Mechanical Specifications

Connection Type: Parallel-hardwired, feed-through dual wire terminal block: Accepts up to #3 AWG wire

Surge Counter: No

Performance Data

MCOV: L-N:150V, L-G:150V, N-G:150V, L-L:300V

VPR: L-N:1000V, L-G:1200V, N-G:800V, L-L:1500V

Protection Mode: 7-Mode

Maximum Surge Current, Per Mode (Per Phase): 100kA (200kA)

Short Circuit Current Rating: 100kA

Nominal Discharge Current Rating: 20kA

Noise Rejection: -20 to -40 dB at 5kHz-10MHz

Diagnostics: Real Time Protection status LEDs & Audible Alarm

Remote Monitoring: Dry Contact Leads-N.O./N.C. Form C Rated at 7Amps @ 240VAC or 30 VDC

Standards and Certifications

UL1449 3rd Edition: cULus Listed Type 2

ANSI/IEEE Category A, B & C: C-62.41 & 62.45

Disconnect Switch: UL 508 and CSA C22.2 #14 compliant (E63822)

Warranty

Product Warranty: Limited Lifetime

Replacement Module Warranty: Limited Lifetime

Product Features

Replaceable Modules: Yes

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

