



Color: White

UPC Code: 07847737412
Country Of Origin: Mexico

NEMA: 5-15P



8256-VJ

Brand Features

When it comes to the demanding nature of today's commercial and industrial electrical environments, ruggedness and ease of installation are the features you look for first in any line of plugs and connectors. Leviton's Python straight-blade plugs and connectors hold up under the most exacting requirements, the toughest conditions, the roughest handling. Python's exceptional design features meet your needs for a quick, easy-to-wire plug and connector system, a must in today's faced-paced world where lost minutes on a job can translate into lost profits.

Item Description

15 Amp, 125 Volt, NEMA 5-15P, 2P, 3W, Plug, Straight Blade, Hospital Grade, Grounding, Python, RoHs Compliant - WHITE

Technical Information

Electrical Specifications

Current Interrupting: Certified for current interrupting at full rated current

Dielectric Voltage: Withstands 2000V

per UL498

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Environment: Dry

Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications

Assembly Screws: Steel, Zinc Plated

Blades/Contacts: Solid Brass

Body Material: Nylon

Mechanical Specifications

Cord Range: .250 - .650

Product ID: Ratings and NEMA I.D. permanently marked on device **Terminal Accom.:** 18-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Product Features

Amperage: 15 A

Assembly Screws: Steel, Zinc Plated

Blades/Contacts: Solid Brass **Body Material:** Nylon

Brand: Python Color: White

Cord Range: .250 - .650

Device Type: Straight Blade Plug

Grounding: Grounding

NEMA: 5-15P **Pole:** 2

Standards and Certifications: UL/CSA

Voltage: 125 VAC Warranty: 2 Year

Wire: 3

Wire Gauge: 18-10 AWG

Standards and Certifications

ANSI: C-73


CSA C22.2 No. 42: File LR-406

NEMA: WD-6 NOM: 057 UL: Listed


Features and Benefits

- Tough high-impact body
- Hinged design delivers fast, easy installation and assembly
- Triple-drive screws for easy wiring Standard, Phillips, Robertson
- Wide Cord Clamp Range, 18-3 SVT-10-3 ST, (.250"-.650")
- Backed by a 2-Year Warranty
- RoHs Compliant

Dimensional Diagram



Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

