



UPC Code : 078477366998

Country Of Origin : Canada



## AGTR1-HGW

Tamper-Resistant Dual Function AFCI/GFCI Receptacle, Hospital Grade, 15 Amp, 125 Volt, White

Hospital Grade AFCI/Self-Test GFCI Tamper-Resistant Receptacle, NEMA 5-15R, 15 Amp 125 Volt Feed-Through, White

SmartlockPro® Dual Function AFCI/GFCI receptacles offer protection both from electrical fires that could result from arc-faults and from electrical shock due to ground faults in one device, satisfying National Electrical Code® (NEC®) requirements for both AFCI and GFCI protection. Tamper-resistant hospital grade versions help satisfy a recent requirement of the Joint Commission, which requires tamper-resistant receptacles with arc fault and ground fault interruption to be installed in all patient accessible areas in behavioral health units.

- Industry-exclusive!
- Status indicator light provides a simple visual indication to the user of the status of AFCI and GFCI protection
- Hospital grade receptacle ensures dependable performance
- Tamper-resistant shutters meet NEC Article 406.12 requirements
- Common Applications: Behavioral Health Units (patient bedrooms, restrooms, corridors, and common spaces) and other Health Care Facilities

### Technical Information

#### Electrical Specifications

**Amperage** : 15 A  
**Dielectric Voltage** : Withstands 1250VAC per UL 1699A  
**Grounding** : Self-Grounding  
**Horsepower Rating** : 1 HP  
**Pole** : 2  
**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current  
**Voltage** : 125 VAC  
**Wire** : 3

#### Environmental Specifications

**Flammability** : Rated V-2 per UL 94  
**Operating Temperature** : -35°C to 66°C

#### Material Specifications

**Body Material** : Polycarbonate  
**Clamps** : Brass  
**Face Material** : Thermoplastic  
**Grounding Screw** : Plated Steel  
**Line Contacts** : Brass Double-Wipe .031 Thick  
**Strap Material** : Galvanized Steel  
**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Screws** : Plated Steel

#### Mechanical Specifications

**Product ID** : Ratings are permanently marked on device  
**Terminal Accom.** : 14-10 AWG  
**Termination** : Back & Side

#### Product Features

**Color** : White  
**Device Type** : Duplex Receptacle Outlet  
**Feature** : Self-Test, Tamper-Resistant  
**Function** : Dual Function AFCI/GFCI  
**NEMA** : 5-15R

#### Standards and Certifications

**ANSI** : C-73  
**CSA C22.2 No. 42** : Yes  
**CSA Technical Information Letter No. M-02A** : Yes  
**NOM** : Yes  
**UL Fed Spec WC-596** : Yes  
**UL1699.A** : File E480630  
**UL498** : Yes

#### Warranty

**Warranty** : 2-Year Limited

## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

