



## Main

Actuation	CW and CCW
Actuator	Lever Arm with Roller
Actuator Action	Momentary
Ampere Rating	10A
Approvals	UL Listed File Number E164353 - CSA Certified File Number 164581 - CE Marked
Body Material	Plastic
Body Type	Compact (Wide) Modular
Connection Type	Conduit Entrance (0.5 Inch NPT)
Contact Configuration	1 N.O./1 N.C.
Contact Material	Silver Alloy
Contact Operation	Snap Action
Enclosure Rating	NEMA 1/2/4/6/12/13; IP66/67
Head Type	Rotary
Lever Arm Length	33 to 83.5mm
Maximum Voltage Rating	240VAC/250VDC
Mounting Type	Panel
Operating Temperature Range	-13 to 158 Degrees F
Operating Torque/Force	14.16 Inch-Ounces (0.10Nm)
Roller Dimension (Diameter X W)	16 x 5.5mm
Roller Material	Thermoplastic
Shock Resistance	50G
Terminal Type	Screw Clamp
Type	XCKT
Type of Duty	General Duty
Vibration Resistance	25G

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.