




Color :

UPC Code: 078477898215
Country Of Origin: China

White



Available Colors :



G5262-TW

Self-Test Tamper-Resistant Industrial Grade GFCI

SmartlockPro Self-Test Tamper-Resistant GFCI Duplex Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Peace of mind, all the time. The SmartlockPro Self-Test GFCI tests itself even if you forget. Designed to meet the latest UL standard for auto-monitoring (self-test) our complete line of self-test GFCIs periodically conduct an automatic internal test to confirm that it can respond to a ground fault. With the slimmest profile on the market, the device allows for fast and easy installation, while Leviton's patented reset lockout mechanism prevents reset of the GFCI if it is not wired or operating correctly. The SmartlockPro Self-Test GFCI is the smart choice in ground fault circuit interrupter protection.

Technical Information

AC Horsepower Ratings
At Rated Voltage: 1 HP
Electrical Specifications

Amperage: 15 A
Grounding: Self-Grounding

Pole: 2

Short Circuit Current Rating: 10kA

Voltage: 125 VAC

Wire: 3

Environmental Specifications

Flammability: Rated V-0 per UL 94

Operating Temperature: -35C to +66C

Material Specifications

Body Material: Polycarbonate

Face Material : PBT Ground Clips : Brass

Grounding Screw: Plated Steel

Line Contacts: Brass

Shutter Mechanism : Delrin® Acetal Strap Material : Galvanized Steel Terminal Clamp : Brass
Terminal Screws : Plated Steel

Mechanical Specifications

Product ID: Ratings are permenantly

marked on device

Termination: Back or Side Wire

Product Features

Brand : SmartlockPro

Color: White

Device Type: Duplex Receptacle Outlet

Feature : Tamper-Resistant, Power Indication

Function : GFCI

Grade: Extra Heavy-Duty Industrial

Specification Grade NEMA: 5-15R

Standards and Certifications

ANSI: C-73

Applicable Standards: UL 943, UL 498, CSA C22.2 No. 42 & 144, FedSpec

W-C-596


Certification/Listing: UL, CSA, NOM-

ANCE

NEMA: WD-1 & WD-6

Warranty

Warranty: 2-Year Limited



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:thm:condition} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

