

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with frame-in LP6 and housings LC6, LI6, L7X, L7XR, L7XF, L7XFR and LI6F.

### CONSTRUCTION

Aluminum one piece reflector.

White polyester powder coat paint with clear anodized upper reflector.

Metal baffles available in black or white.

White finish has integral flange.

Integral flange.

### INSTALLATION

Socket to trim interface.

Retaining clips riveted to top of reflector hold trim inside housing.

Rough-ins with clips retain trims.

### LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

### WARRANTY

1-year limited warranty. Complete warranty terms located at

[www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Actual performance may differ as a result of end-user environment and application.

Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

6" Full Reflector Trim

# 6B3

PREMIUM METAL BAFFLE

Narrow Flange




### Specifications

Height: 7-3/8 (18.7)

Lamp opening: 6 (15.2)

Diameter: 7-5/8 (19.4)

Trim height when used with Non-IC incandescent rough-in



All dimensions are inches (centimeters) unless otherwise indicated.

### ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

**Example: 6B3**

6B3	
Series	Finish
<b>6B3</b>	<b>(blank)</b> Black premium baffle/white reflector
	<b>W</b> White premium baffle/white reflector

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	100 PAR38	LI6
		65 BR40	
		75 A19	
	Fluorescent	13DTT	L7XF
		18TRT	LI6F
26TRT		L7XF, L7XFR	
Non-IC	Incandescent	150 PAR38	LP6, LC6, L7X, L7XR
		120 BR40	
		150 A19	LP6
		100 A19	LC6, L7X, L7XR

